

www.bestsportsfloors.com cdtacinelli@tacinelli.com 1-888-404-WOOD

The Leggero

Low Impact Wood Sports Floor

Description:

6 Mil Polyethylene Vapor Barrier, seams taped, Vinyl Dura-cushion Pads, stapled to bottom, 2" X 3"Pine Sleepers, 4' lengths, 12" on center 3/4" X 2 1/4" Solid Hard Rock Maple Flooring

Features & Benefits:


- Quality Materials, no need to replace in 10-20 years
- •Superior Craftsmanship, built sturdy, won't fall apart
- •All Inclusive Easy to Understand Pricing, simple, less hassles, no nickel and diming
- •Lifetime Limited Warranty, no out of pocket repair bills because of faulty materials or workmanship* (Backed with Over 60 Years Experience)

*does not cover moisture, maintenance or water related problems

Specifications:


specifications.				
SYSTEM TYPE	Floating System	SLAB DEPRESSION	3/8" (10 mm) pad: 25/32" (20 mm) flooring-	5/8" (16 mm) pad: 25/32" (20 mm) flooring-
FLOORING TYPE	Hard Rock Maple or customer choice		2 5/8″ (67mm) 33/32″ (26 mm) flooring- 2 7/8″ (73mm)	2 7/8" (73mm) 33/32" (26 mm) flooring- 3 1/8" (79mm)
ANCHORAGE	No concrete attachment	TESTING LABORATORY	United States Sports Surfacing Laboratory	
SUBFLOOR CONSTURCTION	Sleeper	CERTIFIED TESTING	Laboratory test equipment	
RESILIENCE	PVC Pads	GREEN STATUS	Managed forests, certification available calibrated and certified through the ISSS	





THRESHOLD DETAIL (optional accessory)

Aluminum Threshold 2" (51 mm) Expansion Space Connor 3/8" (10 mm) Duracushion Pad Duracushion sleeper 25/32" x 2-1/4" (20 mm x 57 mm) Laytite Maple Vapor Barrier 2 5/8" (67 mm) EQUIPMENT DETAIL (optional accessory)



Tacinelli Sports Floor Systems P.O. Box 117, Billings, NY 12510 1-888-404-WOOD cdtacinelli@tacinelli.com www.bestsportsfloors.com